

SEAGC 2018 Pre-conference Workshop: Soil Improvement
for Mega Infrastructure, Jakarta, 6 Nov 2018

Vacuum Preloading for Soil Improvement and Land Reclamation Projects

Professor CHU Jian

Director, Centre for Usable Space & Interim Co-Director,
NTU-JTC Industrial Infrastructure Innovation Centre
Nanyang Technological University, Singapore

cjchu@ntu.edu.sg; 65-7904563



School of Civil and Environmental Engineering

Outline

- Background & Principles
- Methods and Case Studies
- Performance Evaluation
- Recent Developments



School of Civil and Environmental Engineering

Why Vacuum Preloading

- Up to 80 kPa of surcharge can be applied quickly on any soft ground without causing stability problems – THE most cost-effective method for land reclamation using soft fill materials.
- It is more economical compared with fill surcharge.
- Water can be collected and treated if the ground is contaminated.




School of Civil and Environmental Engineering

3

Why Vacuum Preloading

- It can be used as either a consolidation or soil stabilization method.



School of Civil and Environmental Engineering

4

After Herve (2015)

Vacuum preloading for land reclamation

When there is a shortage of sand fill for land reclamation, excavated and dredged soil becomes an economical solution. In this case, vacuum preloading is the most suitable method for soil improvement.



More than **190 km²** of land has been reclaimed for the **Tianjin Port** in Tanggu using clay slurry



School of Civil and Environmental Engineering

5

Port of Brisbane



Channel maintenance dredging materials


consisting of river muds capped with sand was used. The thickness of the fill was up to 9 m. The seabed compressible clay was over 30 m.




School of Civil and Environmental Engineering

6

Principles



Vacuum




Fill surcharge

7

PRESENT METHODS

- With membrane
- Without membrane

Membrane Methods: VC or VC + Surcharge



School of Civil and Environmental Engineering


9



School of Civil and Environmental Engineering

Placement of sand blanket and installation of vertical drains

10



School of Civil and Environmental Engineering

Placement of corrugated flexible pipes

11



School of Civil and Environmental Engineering

Installation of 2-3 layers of membrane

12



Placement of a protection layer on top of the membranes



School of Civil and Environmental Engineering

13



Application of vacuum pressure



School of Civil and Environmental Engineering

14




NANYANG
TECHNOLOGICAL
UNIVERSITY

School of Civil and Environmental Engineering

Application of vacuum and fill surcharge together

15




NANYANG
TECHNOLOGICAL
UNIVERSITY

School of Civil and Environmental Engineering

Installation of instruments for field monitoring

16


Case Study: A Storage Yard using Combined Vacuum and Fill Preloading (Yan & Chu, 2005)





- | | | | |
|----|-------------------|----|--------------|
| ⊥ | Settlement gauge | ⊕⊕ | Field vane |
| ▽ | PWP transducer | ⊕ | Inclinometer |
| □ | Multi-level gauge | ⊖ | Piezometer |
| ○● | Borehole | | |



School of Civil and Environmental Engineering



Soil Profile and Soil Properties




School of Civil and Environmental Engineering










Combined loading can reduce lateral displacement



Ground lateral displacement versus time curves


Effect of lateral displacement



School of Civil and Environmental Engineering

27

Use of cutoff walls for sandy layer over soft clay



After Tang and Shang (2000)




School of Civil and Environmental Engineering

28

Membraneless method


When the use of a cut-off wall is too expensive or not feasible, PVD with plastic sleeve or a direct connection of PVD to vacuum tube may be used.




School of Civil and Environmental Engineering

29

Case Study: Soil Improvement at Tuas Singapore




Project Location and soil profile



30

Membraneless VC method



School of
31



Installation of PVD with tubes



NANYANG
TECHNOLOGICAL
UNIVERSITY

School of Civil and Environmental Engineering

32



Summary on membraneless VC

- Great saving on cutoff wall.
- Requires **very detailed SI data** which may be difficult for large scale implementation.
- For the same reason, there can be **short circuits in the VC system** and affect the VC performance.
- The installation is time consuming.
- The vacuum pressure achieved is normally 60 kPa or lower.



School of Civil and Environmental Engineering

35

Degree of Consolidation Calculation

- Based on settlements
- **Based on Pore water pressures**



School of Civil and Environmental Engineering

Methods for Calculating DOC

- Normally based settlement monitored:

$$\text{DOC} = S(t)/S_{\text{ult}}$$

Different methods for estimating S_{ult} has been adopted (Asoaka, Hyperbolic, and Zeng et al.).

- **Based on pore water pressure (PWP) monitored.**

Can be done easily using the following method.




School of Civil and Environmental Engineering

37


Asaoka's method

Note: The results of Asaoka's method is affected by the time interval used (the larger the Δt , the smaller the S_f) and the secondary settlement. **Early plot (with DOC < 70%) may not be reliable.**





School of Civil and Environmental Engineering

38



After
Holtz et
al.
(1991)

Ultimate settlement prediction?




School of Civil and Environmental Engineering

39

Chu et al (2009)

Calculation of DOC using PWP





After Chu and Yan (2005)

$$U_{avg} = 1 - \frac{\int [u_t(h) - u_s] dh}{\int [u_0(h) - u_s] dh}$$



School of Civil and Environmental Engineering

40



DOC Calculated using PWP and Settlement

Degree of consolidation (DOC)	Based on settlement data				Based on pore water pressure data			
	30	60	90	End	30	60	90	End
Case I	-	-	87%	-	-	-	82%	-
Case II	45%	80%	88%	95%	38%	73%	84%	92%



School of Civil and Environmental Engineering


Why DOC_PWP is smaller than DOC_Settlement?

- It is related to how PWP and settlement are measured. When limited instruments are used, instruments will be placed to measure the largest settlement and PWP.
- Settlement is measured at a surcharge lower than specified.
- When DOC (pwp) is more than 85%, the difference tends to be small.



School of Civil and Environmental Engineering

Settlement changes with consolidation pressure



School of Civil and Environmental Engineering

45

Recommendations

- As both settlements and PWP are measured, DOC should be calculated using both settlement and PWP data.
- For vacuum preloading project, PWPs have to be used to evaluate the vacuum pressure applied. Hence, the use of PWPs to evaluate DOC is an essential step.
- A difference between DOC evaluated using settlement and PWP data is understandable as long as a good explanation can be given.



School of Civil and Environmental Engineering

46

RECENT DEVELOPMENTS for the use of vacuum preloading of clay slurry fills for land reclamation



School of Civil and Environmental Engineering

Use of dredged soft soil



School of Civil and Environmental Engineering

48

Difficulties in the use of soft soil/ slurry for land reclamation

- **Major difficulty:** The top surface is too soft for workers and machines to go on top to carry out soft improvement work.
- **Key technical challenge:** *how to form a working platform??*
- **Method to use:** *the one with the lowest unit cost!*



School of Civil and Environmental Engineering

49

Land reclamation and soil improvement method for soft fills

Version 1 –V1

Fill materials:

- *Grabbed lumpy soil for below -3 mCD*
- *Clay slurry or sand for above -3 mCD*


Soil Improvement Method: Use two rounds of Vacuum preloading (VP):

- *R1: Use special VP to consolidate the top 4-5 m of slurry fill to form a working platform*
- *R2: Use conventional VP to improve the whole soft fill layers and the soft seabed soils*



School of Civil and Environmental Engineering

50



Installation of PVD over slurry




Vacuum with membrane, but without sand blanket



School of Civil and Environmental Engineering

53

Fish-bone vacuum preloading (FBVP) without membrane



School of Civil and Environmental Engineering

Guo, Chu, et al, (1916); Sun et al. (2017)

54

Summary

- Vacuum preloading causes an inward lateral movement. Thus, the pressure can be applied instantly without causing any instability problem.
- There are two methods to apply vacuum pressure: with or without the use of membranes. Each has its own advantages and disadvantages.
- Vacuum preloading is applied by reducing the pore water pressure in the soil through the application of a vacuum pressure. The preloading value can only be assessed by measuring the vacuum pressure in the soil. Thus, it is essential to monitor both settlements and pore water pressures in the soil and use both sets of data to estimate the degree of consolidation achieved.
- The key for consolidation of clay slurry is the formation of working platform. A cost-effective method to use two rounds of vacuum preloading is suggested.



School of Civil and Environmental Engineering

55

17TH International Conference on Soil Mechanics & Geotechnical Engineering

State of the Art Report

Construction Processes *Procédés de Construction*

Jian Chu

Nanyang Technological University, Singapore

Serge Varaksin

Menard, France

Ulrich Klotz

Zublin International GmbH, Germany

Patrick Mengé

Dredging International n.v., DEME, Belgium

Chu, J. Varaksin, S. Klotz, U. and Mengé, P. (2009). "Construction Processes." *State-of-the-art Report, 17th International Conference on Soil Mechanics and Geotechnical Engineering*, Alexandria, Egypt, 5-10 Oct. Vol. 4, pp. 3006-3135 (130 pages).




School of Civil and Environmental Engineering

56

Chapter 4

Prefabricated vertical drains

J Chu and VR Raju



CONTENTS

4.1	Introduction	88
4.2	Consolidation theories and analysis	89
4.3	Design	99
4.3.1	Determination of design parameters	100
4.3.2	Properties of smeared soil	104
4.3.3	Types of PVDs	106
4.3.4	Selection of PVDs	108
4.3.4.1	The discharge capacity	109
4.3.4.2	Compatibility of the filter with the soil to be improved	111
4.3.4.3	The tensile strength of drain	112
4.3.5	Pattern, spacing, and penetration depth for PVDs	113
4.3.6	Settlement calculations	113
4.4	Construction	115
4.4.1	Installation	115
4.4.2	Quality-control tests	119
4.4.2.1	Determination of the AOS	121
4.4.2.2	Permeability (or Permittivity) of filter	121
4.4.2.3	Discharge capacity test	124
4.4.2.4	Tensile strength tests	130
4.4.3	Measurement of penetration depth	131
4.4.3.1	Digitised PVD	132
4.4.3.2	PVD with two wires	133
4.4.3.3	PVD with one wire	135
4.4.4	Field instrumentation and evaluation of performance	136
4.5	Design codes, standardisation, and specifications	142
4.6	PVD for vacuum preloading	144
4.7	Case studies	146
4.7.1	Reclamation and soil improvement for a slurry pond in singapore	146



School of Civil and Environmental Engineering

Ground Improvement
3rd Ed, by Krisch and Bell (2013)

School of Civil and Environmental Engineering

58

List of references

1. Chu, J., Varaskin, S., Klotz, U. and Menge, P. (2009). Construction processes, SOA Report, Proc 17th ICSMGE, Alexandria, Egypt, 3006-3135.
2. Bo, M.W., Chu, J., Low, B.K. and Choa, V. (2003). *Soil Improvement: Prefabricated Vertical Drain Technique*, Thomson Learning.
3. Chu, J., Bo, M. W., Chang, M. F., and Choa, V. (2002). "The consolidation and permeability properties of Singapore marine clay." *Journal of Geotechnical and Geoenvironmental Engineering*, ASCE, Vol. 128, No. 9, 724-732.
4. Chu, J., Bo, M. W., and Choa, V. (2004). "Practical considerations for using vertical drains in soil improvement projects." *Geotextiles and Geomembranes*, Vol. 22, 101-117.
5. Bo, M. W., Chu, J., Choa, V. (2005). "Changi East Reclamation and Soil Improvement Project." Chapter 9, In *Ground Improvement – Case Histories*, Eds. B. Indraratna and J. Chu, Elsevier, 247-276.
6. Chu, J., Bo, M. W. and Choa, V. (2006). "Improvement of ultra-soft soil using prefabricated vertical drains." *Geotextiles and Geomembranes*, Vol. 24, 339-348.
7. Chu, J., Bo, M.W., and Arulrajah, A. (2009). "Soil improvement works for an offshore land reclamation." *Geot. Eng. Proc. ICE*, Vol. 162, GE1, 21-32.
8. Chu, J., Yan, S. W., and Yang, H. (2000). "Soil improvement by vacuum preloading method for an oil storage station". *Geotechnique*, Vol. 50, No. 6, 625-632.
9. Chu, J. and Yan, S. W. (2005). "Application of the vacuum preloading method in land reclamation and soil improvement projects." Chapter 3, In *Ground Improvement – Case Histories*, Eds. B. Indraratna and J. Chu, Elsevier, 91-118.
10. Chu, J. and Yan, S. Y. (2005). "Estimation of degree of consolidation for vacuum preloading projects." *Int. Journal of Geomechanics*, ASCE, Vol. 5, No. 2, 158-165.
11. Yan, S. W. and Chu, J. (2005). "Soil improvement for a storage yard using the combined vacuum and fill preloading method" *Canadian Geotechnical Journal*, Vol. 42, No. 4, 2094-1104.
12. Lam KP, Wu S and Chu J (2018). "Field trial of a membraneless vacuum preloading system for soft soil improvement." *Ground Improvement*, <https://doi.org/10.1680/jgrim.17.00081>



School of Civil and Environmental Engineering

59

Acknowledgements

- **My students and researchers:** Drs Li Bing, Guo Wei, Wu Shifan, He Jia, Kou Hailei, Chen Hao, etc.
- **Funding agencies and industries** for the funding supports.

Thank you!



School of Civil and Environmental Engineering

60